

INFEOS

Announcing: Full-Deck Coverage For StormGuard™ And Weather Watch® Leak Barriers!



Now, Consider Full Deck Coverage with Weather Watch® or StormGuard™ Leak Barriers under Fiberglass Asphalt Shingles

The use of full deck coverage with Weather Watch® and StormGuard™ Leak Barriers under fiberglass asphalt shingles provides a major advantage in protecting the roof and building in severe wind and hail events. How? Since they are solidly adhered to the roof deck and self-seal around each nail, leak vulnerability is significantly reduced from causes including wind driven rain and lost or damaged shingles. Simply, these Leak Barriers provide an unsurpassed, sound, and secure secondary roof.

However, to achieve this excellent protection, precautions must be taken.

Weather Watch® and StormGuard™ Leak Barriers are vapor retarders. They prevent the migration of moisture-laden air that reaches the attic and closed ceiling (cathedral ceilings) from travelling through to the

otherwise permeable roof system installed above them.

Typical household activities such as cooking, bathing and humidifying the house generate significant quantities of moisture that generally make their way into the attic area. If the moisture becomes trapped there because of insufficient ventilation, problems can develop.

Therefore, full deck coverage with Leak Barriers may result in moisture-related problems with the roof deck and the structural roof support in the attic. Proper moisture control **must** be used in the attic (or space below the roof deck) in the building when these products are installed over an entire roof deck.

Specifically, excess moisture in the roof deck and attic area can result in:

- Deck movement, causing picture framing which can be seen through shingles.
- Shingle splitting and cracking
- Nail back out
- Mold and mildew growth
- Insect infestation

- Rotting of the deck and structural supports
- Stained and damaged ceilings
- Wet insulation that has reduced insulation value
- Ice in the attic and subsequent water damage when it melts

Precautions

If a Weather Watch® or StormGuard™ Leak Barrier is to be installed to provide full deck coverage, a design professional must address the potential for moisture entrapment, excessive moisture build up and condensation. In designing a proper moisture control system, many factors including building use and moisture sources, as well as expected inside and outside temperatures and relative humidities must be taken into consideration.

Moisture control solutions may include, but are not limited to use of:

- a continuous vapor barrier in the ceiling
- soffit and ridge vents
- gable vents
- power vents

Weather Watch® and StormGuard™ can also be left exposed for up to 60 days!



Quality You Can Trust Since 1886... from North America's Largest Roofing Manufacturer